

"USE CLASS 4" PLANED TIMBER

Manufacturing/composition: Timber planed on all 4 surfaces
Rounded or sharp edges
18-20% drying

Impregnated timber, green or brown, for use in use class 4

Current offer:

Common thicknesses (mm) *	Common widths (mm) *	Common lengths (m) *	Common options (appearance)
22	42		
36	68		Option 2
46	90		
68	120	2.00	
90	145	2.40	Option 1
	190	2.50	On request
46 x 46		3.00	
68 x 68		4.00	
90 x 90			
120 x 120			
145 x 145			

(*) Depending on the supplier

- the timber thickness and width may vary.
- the length may exceed 4.00 m, and can measure up to 6.00 m

Certifications/Labels:

CTB B+ for impregnated timber (quality marking issued by the FCBA attesting to the effectiveness and non-toxicity of the treatment)



Impregnated pine conserves its mechanical properties.



PEFC certified timber on request

CE marking compulsory if for structural use



Reference standards:

NF B50-105-3 "Timber durability – Performance"

Applications:

Treating pine wood in a vacuum and pressure autoclave makes it rot and termite resistant.

In the French overseas territories, impregnated pine is therefore an essential construction and DIY material used in any area correlated by termites. It is also ideal for use in contact with the ground or with soft water.

- Timber swimming pools
- Flower planters, sandboxes
- Outdoor furniture
- Fences, windows, outdoor staircases
- Pontoons, walkways
- Shelters, cabins, canopies
- Ledger strips for terraces, framework for cladding