




"USE 4" DECKING BOARDS

Manufacturing/composition: Planed timber
Rounded edges
Choice of smooth, serrated or grooved surfaces
Impregnated timber, green or brown (depending on choice), for use as use 4

Current offer:

Profiles	Cuts lengths (mm)	Common lengths (m)
Non-exhaustive list		
	22 x 90 (95)	2.40 3.00
	22 x 115 (120)	
	28 x 145	

Each manufacturer has their own profiles

Certification/label: **CTB B+** for impregnated timber (quality marking issued by the FCBA attesting to the effectiveness and non-toxicity of the treatment)



PEFC certified timber on request



Reference standards: **DTU 51.4** "Outdoor timber decking"
NF B54-040 "Decking boards – Characteristics"
NF B52-001 "Structural grading – visual method"
NF B50-105-3 "Timber durability – Performance"

Applications:

- Exposed outdoor terraces
- Swimming pool and flower bed edges
- Walkways
- Beach/sand dune boardwalks

"Use class 4" terrace boards must be placed on floor battens of the same type. (see "framing timber")
Decking boards must be maximum 18% dried before they are used (see DTU 51.4)

Description:

"The decking will be made of solid pine planed boards, manufactured in accordance with the NF B54-040 standard. The wood will have been impregnated in a vacuum pressure autoclave with a green/brown colour product for use in grade 4 (retention level in line with the NF B50-105-3 standard). The boards will be fixed onto pine floor battens that have been through the same impregnation process, using stainless steel screws, and will be arranged with gaps defined by DTU 51.4, depending on the location, age and hygrometry rate of the boards. The cutting of the floor battens, their spacing and the spacing of their supports are also defined in DTU 51.4. "